

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
7 February 2002 (07.02.2002)

PCT

(10) International Publication Number  
**WO 02/09615 A2**

- (51) International Patent Classification<sup>7</sup>: **A61F 2/00**
- (74) Agent: **ISACSON, John, P.**; Heller, Ehrman, White & McAuliffe, 1666 K Street, N.W., Suite 300, Washington, DC 20006 (US).
- (21) International Application Number: **PCT/US01/22638**
- (22) International Filing Date: **19 July 2001 (19.07.2001)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
60/222,049 31 July 2000 (31.07.2000) US  
60/234,345 22 September 2000 (22.09.2000) US  
60/289,528 9 May 2001 (09.05.2001) US
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): **MASSACHUSETTS GENERAL HOSPITAL** [US/US]; Thirteenth Street, Building 149, Suite 5036, Charlestown, MA 02129-2000 (US).
- (71) Applicants and  
(72) Inventors: **HARRIS, William, H.** [US/US]; 665 Concord Avenue, Belmont, MA 02178 (US). **BURROUGHS, Brian, R.** [US/US]; 109A Dartmouth Strasse, Apt.#21, Boston, MA 02114 (US). **HOEFFEL, Daniel, P.** [US/US]; 9180 Heritage Way, Woodbury, MN 55125 (US).
- Published:**  
— *without international search report and to be republished upon receipt of that report*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **IMPROVED ACETABULAR COMPONENTS THAT DECREASE RISKS OF DISLOCATION**



(57) Abstract: The present invention provides monopolar acetabular liners that can enclose a femoral head to form a hip replacement prosthesis, wherein the liner has a rim that creates an orifice, wherein the orifice has a diameter that is smaller than the diameter of the femoral head, and wherein the liner encompasses greater than 50 percent of the volume of the head, wherein a constraining ring can be used in conjunction with the monopolar constrained acetabular liner to provide additional support for the femoral head to stay with the acetabular liner and avoid dislocation. Assemblies, complete prosthetic replacements,

and methods of replacing also are provided. Liners and constraining rings having no, one or more recesses also are provided.

WO 02/09615 A2

1  
2  
3  
4  
5 **IMPROVED ACETABULAR COMPONENTS THAT DECREASE RISKS OF**  
6 **DISLOCATION**

7 This application claims priority to U.S. Serial No. 60/222,049 filed July  
8 31, 2000, U.S. Serial No. 60/234,345 filed September 22, 2000, and U.S. Serial  
9 No. 60/289,528 filed May 9, 2001, which are incorporated by reference.

10 The present invention relates to improved acetabular components, such  
11 as liners, assemblies and complete replacements, for use in the body. The  
12 improved acetabular components can be used, for example, in hip arthroplasties  
13 in both a primary and revision setting. The present invention provides a  
14 decreased risk of dislocation while facilitating greater range of motion  
15 ("ROM").

16 **Description of the Field**  
17

18 Dislocation is a major source of morbidity at re-operation after total hip  
19 arthroplasty. Dislocation rates have been quoted at 1 - 10% for primary total  
20 hip arthroplasties. Many studies have shown increased rates of dislocation after  
21 revision total hip arthroplasty when compared with primary total hip  
22 arthroplasty. Currently, the chance of "successful surgical management of a  
23 recurrent dislocation" is 70% when a cause for the dislocation can be identified.  
24 Dislocation results in significant patient anxiety. In addition, the costs  
25 associated with surgical management of dislocation are significant.

26 A variety of approaches have been used to address dislocation, including  
27 changing the angle of the femoral component, changing the angle of the  
28 acetabular component, using extended lip liners, using off-set liners, advancing

1 the greater trochanter, and using constrained acetabular components. Another  
2 approach is to use femoral heads of larger diameter.

3 Some of these approaches have distinct disadvantages, however.

4 Altering the orientation of the components can increase stability in one  
5 direction (for example, posteriorly) but at the same time decrease stability in the  
6 opposite direction (for example, anteriorly). Use of extended lip liners and  
7 currently available constrained acetabular components which utilize additional  
8 polyethylene to surround the femoral head increases joint stability but this  
9 additional material also can, depending on the design, constrict the range of  
10 motion of the joint and can lead to subsequent problems related to  
11 impingement. When the hip joint is articulated (for example, flexed, extended,  
12 rotated, etc.) to its limit, impingement between the femoral neck and acetabular  
13 liner may occur.

14 Component impingement is undesirable for several reasons. The  
15 femoral neck impinging against the polyethylene liner can produce damage to  
16 the polyethylene as well as increasing the stresses at the component / bone  
17 interface. Additionally, the point of impingement acts as the fulcrum through  
18 which the force produced by the leg could lever the femoral head out of the  
19 liner and hence lead to dislocation.

20 Many current methods of reducing the risk of dislocation, including  
21 recurrent dislocation, employ the use of so called "constrained liners," which  
22 are complex bipolar or tripolar articulations. In a study of twenty one  
23 constrained acetabular components to treat preoperative or intraoperative  
24 instability, six patients had recurrent dislocations. It was postulated that this  
25 increase was caused by the impingement of the femoral stem on the rim of the  
26 insert due to decreased range of motion within the design. Orthopaedic  
27 Knowledge Update, Chapter 38, page 474 (James H. Beatty, M.D., editor,  
28 AAOS).

1           Constrained systems that are currently available use ultra high molecular  
2 weight polyethylene (UHMWPE) which is not crosslinked. A major limitation  
3 of the material is it's high wear rate and the risk of periprosthetic osteolysis.  
4 Also, their stated range of motion in flexion is between 72° and 90°. Such  
5 devices are available from Zimmer, Inc., Johnson & Johnson/Depuy Inc., and  
6 Howmedica-Osteonics, Inc.

7           The current products have additional limitations. For example, the  
8 Osteonics system utilizes only 22, 26 and 28 mm heads. The minimum  
9 diameter of the acetabular shell is 50 mm. This design is "bipolar." A bipolar  
10 system is made up of a acetabular shell with a polyethylene liner, and inside of  
11 that liner is a metal head. Inside of that metal head is another polyethylene  
12 liner, which in turn captures a 22, 26, or 28 mm head that is attached to the  
13 femoral stem. Thus, the Osteonics system has multiple polyethylene on metal  
14 articulations. The multiple articulations generate polyethylene wear debris at a  
15 much faster rate than designs with a single metal on polyethylene articulation.  
16 Additionally, the range of motion only is approximately 90 degrees.

17           A constrained system developed by Zimmer, Inc. uses a metal shell with  
18 a two-piece polyethylene liner. One piece is inserted into the acetabular metal  
19 shell followed by placement of the other portion around the neck on the femoral  
20 component before the femoral head has been put on the Morse taper. The head  
21 is then reduced into the acetabular component. The polyethylene portion with a  
22 metal band that is around the femoral neck is then brought into contact with the  
23 acetabular polyethylene component and the metal band then secured to  
24 "capture" the head within the assembled polyethylene liner. Again, this design  
25 uses ultra high molecular weight polyethylene and can generate significant  
26 debris as well as a limited range of motion. The limited range of motion results

1 in impingement in flexion, which generates a rotational torque at the bone shell  
2 interface, potentially inhibiting bony in-growth into the acetabular shell.

3 In the late 1960's to early 1970's, others attempted to implant a  
4 cemented conventional UHMWPE liner with greater than 50% head coverage.  
5 Lagrange and Letournel, *Int Surg.* 60(1):21-4 (1975); Lanzetta, *Arch Ortop.*  
6 83(1):49-53 (1970). These designs had a 35mm inner diameter and was  
7 available in only two (47 and 58mm) outer diameters. These approaches,  
8 however, did not yield a replacement with acceptable performance. Long-term  
9 data is not available for the LaGrange/Letournel design, likely because it did  
10 not become a widely-accepted product. Its head design (35 mm diameter) in  
11 conjunction with conventional UHMWPE available at the time would have had  
12 a substantial wear rate.

13 Thus, current and past designs have utilized various approaches,  
14 including countersinks, in which the center of rotation of the femoral head is  
15 below the level of the flat surface of the liner. Yet even the use of a  
16 countersink design using large head diameters is less than optimal because,  
17 among other things, these liners did not have an orifice that was less than the  
18 diameter of the femoral head, and therefore have no mechanical capture, and  
19 took no other steps to avoid or minimize dislocation.

20 It has been shown that larger heads are effective in reducing the rate of  
21 recurrent dislocations, even when used with conventional polyethylene.  
22 Amstutz *et al.*, 12th Annual International Symposium for Technology in  
23 Arthroplasty, ISTA '99, Chicago, IL (1999). However, hip simulator studies  
24 have shown that the wear of conventional polyethylene with the larger heads is  
25 excessive. This disadvantage was demonstrated *in vivo* by the results of surface  
26 replacement as well. Amstutz *et al.*, *Clin. Orthop.* 213: 92-114 (1986). In  
27 addition, simply using a large head diameter does not produce mechanical  
28 capture of the femoral head.

1           In achieving some of the advantages of the invention, in accordance with  
2 one aspect of the invention, there are provided liners with one or more recesses.  
3 The type of recesses according to the present invention, however, are different  
4 than that of the unconstrained Modell St. Georg / Mark I & II and ENDO-  
5 Modell liner, which was to "prevent irritation of the psoas muscle and enable(s)  
6 removal of cement," rather than for reducing dislocation or impingement. See  
7 Englebrecht E, Siegel A, Kluber D: The Modell St. Georg/Mark I/Mark II  
8 Prosthesis. p. 66. In: Finerman G, Dorey F, Grigoris P, McKellop H (eds): Total  
9 Hip Arthroplasty Outcomes. Churchill Livingstone, New York, 1998.

10           In view of the limitations of the commercialized designs, new  
11 approaches are needed that would increase the inherent stability of the head-  
12 liner articulation while at the same time increasing range of motion, which  
13 would result in a decreased rate of dislocation for both primary and revision  
14 total hip arthroplasties. Such approaches would decrease patient anxiety,  
15 eliminate the need for postoperative dislocation precautions, and reduce the  
16 number of revisions performed for dislocation and recurrent dislocation  
17 resulting in a net cost savings to the healthcare system. Such risks of  
18 dislocation are markedly reduced while range of motion is increased,  
19 particularly when a large-head design and/or recesses are employed.

20           Cut away monopolar constrained acetabular liners (US Serial Nos.  
21 60/222,049 and 60/234,345) for use in total hip replacement to help reduce the  
22 potential of dislocation of the hip while still providing sufficient range of  
23 motion for daily activities have been developed. The invention disclosed herein  
24 also provides a separate constraining ring that can be used in conjunction with  
25 the monopolar constrained acetabular liner and the cut away monopolar  
26 constrained acetabular liner to provide additional support for the femoral head  
27 to stay with the acetabular liner and avoid dislocation.

28

### Summary of the Invention

It is an object of the invention to provide improved prostheses for use in the hip. In accomplishing this and other objects, there is provided in accordance with one aspect of the present invention a monopolar acetabular liner that can enclose a femoral head to form a hip replacement prostheses, wherein the liner has a rim that creates an orifice, and wherein the orifice has a diameter that is smaller than the diameter of the femoral head. The rim extends beyond the center line of the head (such as the center of rotation) when the head is enclosed by the liner, and thereby the head is constrained from dislocation. The liner can, in certain embodiments, include one or more recesses or cut-aways to facilitate additional range of motion or be without recess or cut away for use with liners that likewise lack a recess or cut away. The liner, in another embodiment, is designed to accommodate proper fitting of a constraining ring that can be used in conjunction with the monopolar constrained acetabular liner and the cut away monopolar constrained acetabular liner. In accordance with another embodiment, there is provided a constraining ring that can be used in conjunction with the monopolar constrained acetabular liner and the cut away monopolar constrained acetabular liner. The constraining rings provide additional support for the femoral head to stay with the acetabular liner and avoid dislocation. Preferably, the liner comprises ultra high molecular weight polyethylene, that more preferably is all or in part cross-linked. Preferably, the cross-linking is performed via irradiation. The femoral head can have a large diameter. The constraining ring can, in certain embodiments, include one or more recesses or cut-aways to be compatible with the corresponding liner. Alternatively, the constraining ring will be without a recess or cut away for use with liners that likewise lack a recess or cut away.

1           In accordance with another aspect of the present invention, there is  
2 provided a monopolar acetabular assembly comprising (A) a monopolar  
3 acetabular component that encloses a femoral head, wherein the liner has a rim  
4 that creates an orifice, and wherein the orifice has a diameter that is smaller  
5 than the diameter of the femoral head; and (B) a metal shell. The rim extends  
6 beyond the center line of the head (such as the center of rotation) when the head  
7 is enclosed by the liner, and thereby the head is constrained from dislocation.  
8 The liner can, in certain embodiments, include one or more recesses or cut-  
9 ways to facilitate additional range of motion or be without recess or cut away;  
10 and a constraining ring which can be used in conjunction with the monopolar  
11 constrained acetabular liner and the cut away monopolar constrained acetabular  
12 liner to provide additional support for the femoral head to stay with the  
13 acetabular liner and avoid dislocation. The constraining ring, which can be  
14 made from a number of high strength materials (for example, cobalt chrome  
15 alloy, titanium, stainless steel, etc.), is designed to fit around the perimeter of  
16 the liner. The constraining ring, in another embodiment, is designed to fit  
17 properly in conjunction with the monopolar constrained acetabular liner and the  
18 cut away monopolar constrained acetabular liner. Preferably, the liner  
19 comprises ultra high molecular weight polyethylene, that preferably is all or in  
20 part cross-linked. Preferably, the cross-linking is performed via irradiation.  
21 Preferably, the femoral head has a large diameter. The constraining ring can, in  
22 certain embodiments, include one or more recesses or cut-aways to be  
23 compatible with the corresponding liner. Alternatively, the constraining ring  
24 will be without a recess or cut away for use with liners that likewise lack a  
25 recess or cut away. In accordance with the invention, the constraining ring is  
26 preferably made of high strength materials such as cobalt chrome alloy,  
27 titanium, or stainless steel.



1           In accordance with still another aspect of the present invention, there is  
2 provided a hip joint replacement assembly comprising (A) a monopolar  
3 acetabular liner that encloses a femoral head, wherein the liner has a rim that  
4 creates an orifice, and wherein the orifice has a diameter that is smaller than the  
5 diameter of the femoral head; (B) a metal shell; and (C) a femoral head. The  
6 rim extends beyond the center line of the head (such as the center of rotation)  
7 when the head is enclosed by the liner, and thereby the head is constrained from  
8 dislocation. The liner can, in certain embodiments, include one or more  
9 recesses or cut-aways to facilitate additional range of motion or be without  
10 recess or cut away; and a constraining ring which can be used in conjunction  
11 with the monopolar constrained acetabular liner and the cut away monopolar  
12 constrained acetabular liner to provide additional support for the femoral head  
13 to stay with the acetabular liner and avoid dislocation. The constraining ring, in  
14 another embodiment, is designed to fit properly in conjunction with the  
15 monopolar constrained acetabular liner and the cut away monopolar constrained  
16 acetabular liner. Preferably, the liner comprises ultra high molecular weight  
17 polyethylene, that preferably is all or in part cross-linked. Preferably, the cross-  
18 linking is performed via irradiation. The metal shell may be made of titanium,  
19 stainless steel, or a cobalt chrome alloy. Preferably, the femoral head has a  
20 large diameter. The constraining ring can, in certain embodiments, include one  
21 or more recesses or cut-aways to be compatible with the corresponding liner.  
22 Alternatively, the constraining ring will be without a recess or cut away for use  
23 with liners that likewise lack a recess or cut away.

24           In accordance with the invention, metal shells preferably are made of  
25 titanium, cobalt chrome alloys, or stainless steel. The femoral stems preferably  
26 also may be made of a cobalt chrome alloys, stainless steel, or titanium.  
27 Preferably, the femoral heads are made of a cobalt chrome alloys, stainless steel

1 or ceramic. Where the femoral head and stem are one piece, preferably they are  
2 made of a cobalt chrome alloy or stainless steel.

3 In accordance with still a further aspect of the invention, there are  
4 provided methods of replacing a hips in patients in need thereof, comprising the  
5 step of surgically implanting in a given patient a monopolar acetabular liner  
6 that can enclose a femoral head to form a hip replacement prostheses, wherein  
7 the liner has a rim that creates an orifice, and wherein the orifice has a diameter  
8 that is smaller than the diameter of the femoral head, and thereby the head is  
9 constrained from dislocation. The liner can, in certain embodiments, include  
10 one or more recesses or cut-aways to facilitate additional range of motion or be  
11 without recess or cut away; and a constraining ring which can be used in  
12 conjunction with the monopolar constrained acetabular liner and the cut away  
13 monopolar constrained acetabular liner to provide additional support for the  
14 femoral head to stay with the acetabular liner and avoid dislocation. The  
15 constraining ring, in another embodiment, is designed to fit properly in  
16 conjunction with the monopolar constrained acetabular liner and the cut away  
17 monopolar constrained acetabular liner. Implantation of assemblies and total  
18 replacements, such as shells, femoral heads and femoral stems, also are  
19 provided.

20 In contrast to current bipolar and tripolar constrained components the  
21 monopolar constrained design has: (i) increased range of motion, (ii) decreased  
22 wear of the articulation, (iii) simpler intraoperative assembly, (iv) decreased  
23 risk of impingement of the femoral neck upon the liner rim, (v) decreased stress  
24 transfer to the acetabular component-cement interface, (vi) decreased stress  
25 transfer to the cement-bone interface, (vii) decreased stress transfer to the metal  
26 shell-bone interface, (viii) eliminates the thin polyethylene articulating surfaces  
27 associated with multi-polar designs, (ix) eliminates multipolar locking rings,  
28 which have had reported malfunctions and failure, (x) allows for the use of

1 large head diameters, (xi) has smaller possible acetabular shell outer diameters,  
2 (xii) utilizes thicker polyethylene bearing surfaces, (xiii) and further facilitate  
3 range of motion in preferred directions.

4 In contrast to the Legrange /Letournel design, the monopolar constrained  
5 design according to the invention has: (i) a different and superior bearing  
6 surface, (ii) larger head diameters, (iii) decreased wear, (iv) increased ROM, (v)  
7 the capacity to be use in cemented or bony in-growth acetabular replacements,  
8 (vi) thicker polyethylene bearing surfaces, (vii) modularity for use with  
9 uncemented acetabular shells, (viii) can be easily exchanged at the time of  
10 primary or revision surgery, and (ix) and can be designed to facilitate  
11 movement in preferred directions.

12 Although large head diameters with standard UHMWPE bearing  
13 surfaces have been used for the treatment of dislocation and recurrent  
14 dislocation by Amstutz *et al.* In contrast to the designs employed by Amstutz,  
15 the monopolar constrained has: (i) has a mechanical capture of the femoral  
16 head, (ii) reduced wear, (iii) decreased periprosthetic osteolysis, (iv) modularity  
17 for easy conversion between different amounts of constraint, and (v) can be  
18 designed to facilitate movement in preferred directions.

19 In embodiments employing the recesses, the liner can have one or more  
20 recess. A recess, often referred to herein as a cut away, can be positioned to  
21 further facilitate movement in a desired direction.

22 Embodiments employing a constraining ring can be used in conjunction  
23 with the monopolar constrained acetabular liner and the cut away monopolar  
24 constrained acetabular liner to provide addition restraint against dislocation of  
25 the hip joint while at same time not impeding the range of motion of the hip  
26 joint. The constraining ring, in another embodiment, is designed to fit properly  
27 in conjunction with the monopolar constrained acetabular liner and the cut  
28 away monopolar constrained acetabular liner.

1       The constraining ring can be secured to the acetabular liner by means of  
2 a number of locking mechanisms that are similar to those that are currently used  
3 to secure acetabular liners into their mating metal acetabular shell.  
4 Embodiments of this invention have used a locking mechanism which relies on  
5 the spatial interference between the polyethylene acetabular liner and the metal  
6 acetabular shell. This invention is not limited by the use of the locking  
7 mechanism used in such embodiments and the use of other locking mechanisms  
8 are possible.

9       In another embodiment of this invention have used a locking mechanism  
10 which relies on the spatial interference between the polyethylene acetabular  
11 liner and the metal constraining ring. As the constraining ring is being seated  
12 onto the acetabular liner the polyethylene must deform as it moves past a ridge  
13 on the constraining ring. Once the ring is fully seated then the deformed  
14 polyethylene relaxes behind the ridge hence securing the constraining ring to  
15 the liner. This invention is not limited by the use of the locking mechanism  
16 used in such embodiments and the use of other locking mechanisms are  
17 possible. Yet in another the constraining ring can also be fastened to the  
18 acetabular liner by direct screw fixation where screws are passed directly  
19 through the constraining ring into the polyethylene liner.

20       In another embodiment of this invention the constraining ring can be  
21 secured to the liner by means of a retaining ring which is designed in an  
22 unstressed state to sit in grooves in both the constraining ring and acetabular  
23 liner. Upon setting the constraining ring onto the liner the retaining will deform  
24 until the constraining ring is fully seated onto the liner at which point the  
25 retaining ring relaxes into the designed groove in the liner.

26       The constraining ring can, in certain embodiments, include one or more  
27 recesses or cut aways to be compatible with the corresponding liner.

1 Alternatively, the constraining ring will be without a recess or cut away for use  
2 with liners that likewise lack a recess or cut away.

3 These and other aspects of the present invention will become apparent to  
4 the skilled person in view of the description set forth below.

5

6

### **Brief Description of the Figures**

7

8 Figure 1 is a schematic view of a monopolar liner in functional relation  
9 with a femoral head and neck.

10 Figure 2 is a perspective view of a monopolar liner containing 2 recesses  
11 to facilitate greater range of motion.

12 Figure 3 depicts the components of the cut away monopolar constrained  
13 acetabular system with a constraining ring: metal acetabular shell (52) which is  
14 secured to the acetabulum, polyethylene cut away monopolar constrained  
15 acetabular liner (54), and constraining ring (56). Note the metal acetabular  
16 shell is not essential for this invention as the acetabular liner can be directed  
17 secured into the acetabulum with bone cement.

18 Figure 4 depicts constraining rings (56) in different perspectives.

19

20

### **Detailed Description of Aspects of the Invention**

21

22 The present invention decreases the risk of dislocation of total hip  
23 arthroplasty in both the primary and revision setting. See U.S. Serial No.  
24 60/222,049, filed July 31, 2000, and U. S. Serial No. 60/234,345, filed  
25 September 22, 2000, the entirety of which are hereby incorporated by reference.  
26 In conjunction with large diameter femoral heads, such as disclosed in  
27 PCT/US99/16070 (the entirety of which is hereby incorporated by reference),  
28 the present invention can achieve a range of motion that is greater than is

1 currently available so called "constrained" systems using 22, 26, 28 and 32 mm  
2 heads. A decrease in the rate of dislocation will have a positive effect on  
3 patient satisfaction as well as hospital re-admission for treatment of dislocation.  
4 The increased range of motion in this invention will afford patients a more  
5 normal life style than the currently available constrained systems. The present  
6 invention can be surgically implanted in a patient in the same or similar manner  
7 as currently employed implants. Thus, the present invention results in an  
8 improved quality of life as well as improved patient satisfaction.

9 The present invention advantageously employs UHMWPE liners,  
10 preferably using UHMWPE that is cross-linked, including highly cross-linked  
11 UHMWPE. UHMWPE can be cross-linked by a variety of approaches,  
12 including those employing cross-linking chemicals and/or irradiation. Preferred  
13 approaches for cross-linking employ irradiation, and are taught in  
14 PCT/US97/02220, the entirety of which is hereby incorporated by reference.

15 According to the invention, there is preferably a two part acetabular  
16 assembly, namely a metal shell for bony in-growth with UHMWPE liner,  
17 preferably where the bearing surface of the liner that comes into contact with  
18 the femoral head is comprised of crosslinked UHMWPE.

19 The liner of the present invention preferably is "monopolar" system.  
20 The monopolar constrained acetabular preferably has a one piece design and  
21 has a single metal to polyethylene articular surface, and thus preferably is not  
22 bipolar or tripolar in design. The monopolar design allows for the use of  
23 thicker polyethylene in the acetabular liner. Compared to the bipolar and  
24 tripolar constrained/captured designs, the monopolar design decreases the  
25 surface area of contact between metal and polyethylene because there is only  
26 one metal-polyethylene articulation, rather than two or more found in other  
27 designs. Moreover, the use of crosslinked UHMWPE will decrease the amount  
28 of debris particles generated to articulation. Moreover, in the modular form of

1 this acetabular design, since the polyethylene component is not cemented into  
2 place, some revision surgeries are more feasible. Moreover, with the modular  
3 design different types of heads and liners can be used with the shell, and can be  
4 selected by the surgeon during surgery.

5 According to one aspect of the invention, more than 50% of the volume  
6 of the femoral head is enclosed within the polyethylene liner. The diameter of  
7 the opening/orifice of the polyethylene liner is less than the diameter of the  
8 femoral head that is inserted, as shown in Figure 1.

9 Figure 1 depicts at (10) a liner (12) in functional relation with a femoral  
10 head (14) and neck (20). The rim surface (16) of the liner (12) extends beyond  
11 the center line (18), representing the center of rotation of both the femoral head  
12 and the acetabular liner. Preferably the liner rim surface is flat in this  
13 embodiment. The inner portions of the rim circumscribe the orifice. If desired,  
14 a metal shell, not pictured, would be positioned between the liner and the bone  
15 at the mount site, and preferably is configured so as to promote in-growth of the  
16 bone.

17 Figure 2 depicts at (30) a type of recessed or cut away liner (32). In the  
18 pictured embodiment, the rim surface (34) is interrupted by two cut aways (36)  
19 which permit greater range of motion while preserving a constraint to hold a  
20 head in place by a snap fit. Region (38) shows that the rim surface (34) of the  
21 liner (32) extends beyond the center line (not specifically depicted) in such a  
22 manner that the opening/orifice of the liner (32) is less than the diameter of the  
23 femoral head that is inserted therein. Thus, the inner portions of the rim  
24 circumscribe the orifice in such a manner that the head is held within the liner.  
25 If desired, a metal shell, not pictured, would be positioned between the liner  
26 and the bone at the mount site, and preferably is configured so as to promote in-  
27 growth of the bone.

1           The embodiments that employ one or more recesses can have the  
2 recesses positioned to further facilitate movement in a desired direction. For  
3 example, a liner might have a single recess to provide increased range of  
4 motion in flexion. Another arrangement can be a liner with two recesses with  
5 the second recess to provide increased range of motion in extension and/or  
6 extension plus external rotation. Moreover, the increased range of motion  
7 provided by the cut-away design also allows for greater tolerance for the  
8 variations in the orientation of the acetabular component that can occur during  
9 insertion.

10           As stated above, recesses can be positioned to further facilitate  
11 movement in a desired direction, such as in the common directions of  
12 impingement. Recesses can be placed in several different positions, but  
13 preferentially would be placed in the position to produce the range of maximum  
14 motion in a desired direction. For example, in a left hip, when looking at the  
15 acetabular component in position and considering it to be the face of a clock,  
16 the recess would be preferentially placed at about 1-2 o'clock. Under similar  
17 circumstances one would place a recess for a right hip at about 10-11 o'clock.  
18 Recesses in these positions assist with flexion alone and flexion plus internal  
19 rotation. For embodiments with two or more recesses, at least one recess also  
20 would be placed in the position to maximize extension alone and extension plus  
21 external rotation, and thus these recesses would be placed at about 4-5 o'clock  
22 in the left hip and about 7-8 o'clock in the right hip.

23           The recesses preferably are of sufficient size to accommodate the  
24 femoral head and stem (including the neck), while still constraining the head  
25 within the liner. The size of the recess in terms of width and depth depend  
26 upon the size of the stem neck and the range of motion of motion sought, which  
27 are readily determinable by the skilled person based upon a patient's size, age  
28 and needs. If the liner is comprised of a cross-linked polymer, like irradiated



1 ultra high molecular weight polyethylene, then the recesses preferably are  
2 machined into the liner. The liner, in another embodiment, is modified to  
3 accommodate a constraining ring that can be used in conjunction with the  
4 monopolar constrained acetabular liner and the cut away monopolar constrained  
5 acetabular liner to provide additional support for the femoral head to stay with  
6 the acetabular liner and avoid dislocation.

7 Figure 3 depicts at (50) a type of constraining ring (56). In the pictured  
8 embodiment, showing components of the cut away monopolar constrained  
9 acetabular system with a constraining ring: optional metal acetabular shell  
10 which is secured to the acetabulum (52), polyethylene cut away monopolar  
11 constrained acetabular liner (54), and the constraining ring (56). It is notable  
12 that the metal acetabular shell is not essential for this invention as the  
13 acetabular liner can be directed secured into the acetabulum with bone cement.  
14 If desired, the metal shell (52), would be positioned between the liner and the  
15 bone at the mount site, and preferably is configured so as to promote in-growth  
16 of the bone.

17 Figure 4 depicts at (70) a constraining ring (56) shown in different  
18 perspectives.

19 The opening in the monopolar constrained acetabular liner and the cut  
20 away monopolar constrained acetabular liner through which the femoral head  
21 passes upon reducing the femoral head into the liner is smaller than the femoral  
22 head, which allows a snap-fit. Therefore, the constrained liner, which is  
23 typically made of polyethylene, must deform slightly to allow the femoral head  
24 to be embraced by the liner. The constraining ring, which can be made from a  
25 number of high strength materials (for example, cobalt chrome alloy, titanium,  
26 stainless steel, etc.), is designed to fit around the perimeter of the monopolar  
27 constraining acetabular liner and is intended to serve as a structural support of

1 the liner to further ensure that the femoral head will stay within the acetabular  
2 liner.

3 The constraining ring is circular in shape and has "cutouts" similar to  
4 that of the cut away monopolar constrained acetabular liner (Figure 3 & 4).  
5 This prevents the constraining ring from interfering with the range of motion of  
6 the hip.

7 The constraining ring is preferably designed to be a single piece which  
8 can be set onto the acetabular liner during the operative procedure after the  
9 femoral head has been snap-fitted into the acetabular liner. This allows for the  
10 femoral head to stay snapped within the constrained liner.

11 The constraining ring can, in certain embodiments, include one or more  
12 recesses or cut-aways to be compatible with the corresponding liner.  
13 Alternatively, the constraining ring will be without a recess or cut away for use  
14 with liners that likewise lack a recess or cut away.

15 Gross sliding or micro motion between separate metallic surfaces of the  
16 total hip components can generate wear debris which upon release into the joint  
17 space can elicit a biological response that can lead to the development of  
18 osteolysis and hence increasing the of potential of component loosening. The  
19 design of the constraining ring and the acetabular liner are such that to prevent  
20 contact between metallic surfaces. The constraining ring is designed to fit  
21 properly in conjunction with the monopolar constrained acetabular liner and the  
22 cut away monopolar constrained acetabular liner.

23 The components are designed such that the femoral neck will impinge  
24 against the polyethylene liner and not the metallic constraining ring in all  
25 directions of motion. Also, the constraining ring fastens directly to the  
26 polyethylene acetabular liner and has no direct contact with the metal shell into  
27 which the liner is set. Another advantage to this feature is that the use of the  
28 constraining ring is not dependent on the use of a metal shell, hence allowing

1 this system to be used with an acetabular liner which is cemented directly into  
2 the acetabulum.

3 The constraining ring (see Figures 3 & 4) can be secured to the  
4 acetabular liner by means of a number of locking mechanisms which are  
5 currently used to secure acetabular liners into their mating metal acetabular  
6 shell. Embodiments of this invention have used a locking mechanism which  
7 relies on the spatial interference between the polyethylene acetabular liner and  
8 the metal acetabular shell. This invention is not limited by the use of the  
9 locking mechanism used in such embodiments and the use of other locking  
10 mechanisms are possible.

11 In another embodiment of this invention have used a locking mechanism  
12 which relies on the spatial interference between the polyethylene acetabular  
13 liner and the metal constraining ring. As the constraining ring is being seated  
14 onto the acetabular liner the polyethylene must deform as it moves past a ridge  
15 on the constraining ring. Once the ring is fully seated then the deformed  
16 polyethylene relaxes behind the ridge hence securing the constraining ring to  
17 the liner. This invention is not limited by the use of the locking mechanism  
18 used in such embodiments and the use of other locking mechanisms are  
19 possible and contemplated by the invention.

20 Yet in another the constraining ring can also be fastened to the  
21 acetabular liner by direct screw fixation where screws are passed directly  
22 through the constraining ring into the polyethylene liner.

23 In another embodiment of this invention the constraining ring can be  
24 secured to the liner by means of a retaining ring which is designed in an  
25 unstressed state to sit in grooves in both the constraining ring and acetabular  
26 liner. Upon setting the constraining ring onto the liner the retaining will deform  
27 until the constraining ring is fully seated onto the liner at which point the  
28 retaining ring relaxes into the designed grove in the liner.

1       The constraining ring can, in certain embodiments, include one or more  
2       recesses or cut-aways to be compatible with the corresponding liner.  
3       Alternatively, the constraining ring will be without a recess or cut away for use  
4       with liners that likewise lack a recess or cut away.

5       Description of the Assembly of Cut Away Monopolar Constrained  
6       Acetabular Liner with Constraining Ring (see Figure 3): Components of the cut  
7       away monopolar constrained acetabular system consisting of: i) metal  
8       acetabular shell which is secured to the acetabulum, ii) polyethylene cut away  
9       monopolar constrained acetabular liner, and iii) constraining ring. The metal  
10      acetabular shell is not essential for this invention as the acetabular liner can be  
11      directed secured into the acetabulum with bone cement. The cut away  
12      monopolar constrained acetabular liner is set into the metal acetabular. The  
13      constraining ring is placed over the femoral component and the femoral head is  
14      snap-fitted into the acetabular liner. The constraining ring is then set onto the  
15      cut away monopolar constraining acetabular liner with the cutouts of the  
16      constraining ring aligned with the cutouts of the acetabular liner.

17      Demonstration of the Position of the Acetabular Component within the  
18      Hip and Range of Motion: The actual position of the acetabular component  
19      within the hip will be set during the operative procedure and will depend on the  
20      patient's anatomy and gait. The cut away portion of the acetabular component  
21      allows for sufficient range of motion in flexion. The cut away portion of the  
22      acetabular component allows for sufficient internal rotation at 90° of flexion.  
23      The cut away portion of the acetabular component allows for sufficient external  
24      rotation at neutral flexion.

25      In any of the embodiments of the invention, the liners of the invention  
26      can be used with hemispherical and non-hemispherical acetabular shells.

27      Also, the invention can be used with any head diameter, including large  
28      head diameters (for example, 35 mm or greater, such as 38 mm, 40 mm, 42

1 mm, 44 mm, and any diameter in between or larger) in order to increase the  
2 range of motion in comparison with currently available constrained systems.

3 The invention is further demonstrated by the following example, which  
4 do not limit the invention in any manner.

5

6

### Example 1

7

8 The load required for insertion and dislocation of femoral heads in a  
9 constrained liner according to the invention was quantified by inserting 32 and  
10 38 mm heads into simulated liners of electron beam crosslinked UHMWPE.  
11 Two and three dimensional modeling was performed to assess ROM and  
12 stability *in vitro*. The liner had no chamfer.

13 The ROM, and the loads required for insertion and dislocation using  
14 different opening diameters for 32 mm and 38 mm heads in simulated  
15 monopolar liners were measured. A 32 mm head with a 31 mm liner opening  
16 required 60 lbs. for insertion and 55 lbs. for dislocation. When the opening was  
17 increased to 31.5 mm the forces for insertion and dislocation decreased to 29  
18 lbs., and 24 lbs., respectively. Testing of 35.5 mm, 36.5 mm, and 37.5 mm  
19 openings with a 38 mm head was performed. The insertional loads were 157,  
20 130, and 28 lbs. The force necessary to produce dislocation of the femoral head  
21 were 135, 126, and 28 lbs., respectively.

22

23 The ROM for the 38 mm head and a 35.5mm orifice liner is 110°. This  
24 increases to 118° and 131° as the orifice diameter is increased to 36.5 and 37.5  
25 mm. The 32 mm head and 31 mm orifice liner has 116° ROM. The ROM  
26 increases to 124° when a 31.5 mm orifice is used with the 32 mm head.

27

28 These data demonstrate that the constrained design according to the  
invention can minimize the occurrence of dislocation, even with heads and  
liners that are constructed to permit enhanced range of movement.

1           It is to be understood that the description, specific examples and data,  
2 while indicating exemplary embodiments, are given by way of illustration and  
3 are not intended to limit the present invention. Various changes and  
4 modifications within the present invention will become apparent to the skilled  
5 artisan from the discussion, disclosure and data contained herein, and thus are  
6 considered part of the invention.

7

8

**What is claimed is:**

1. A monopolar acetabular liner that can enclose a femoral head to form a hip replacement prostheses, wherein the liner has a rim that creates an orifice, and wherein the orifice has a diameter that is smaller than the diameter of the femoral head.
2. The liner according to claim 1, wherein the rim extends beyond the center line of the head when the head is enclosed by the liner.
3. The liner according to claim 1, wherein the liner comprises polyethylene.
4. The liner according to claim 3, wherein comprises ultra high molecular weight polyethylene.
5. The liner according to claim 4, wherein ultra high molecular weight polyethylene is cross-linked.
6. The liner according to claim 5, wherein the cross-linking is performed via irradiation.
7. The liner according to claim 1, wherein the femoral head has a large diameter.
8. The liner according to claim 1, wherein the liner has at least one recess.
9. A monopolar acetabular assembly comprising
  - (A) a monopolar acetabular liner that encloses a femoral head, wherein the liner has a rim that creates an orifice, and wherein the orifice has a diameter that is smaller than the diameter of the femoral head; and
  - (B) a metal shell.
10. The assembly according to claim 9, wherein the rim extends beyond the center line of the head when the head is enclosed by the liner.
11. The assembly according to claim 9, wherein the metal shell is made of titanium or chrome cobalt .

12. The assembly according to claim 9, wherein the femoral head has a large diameter.
13. The assembly according to claim 9, wherein the liner has at least one recess.
14. A hip joint replacement assembly comprising
  - (A) a monopolar acetabular liner that encloses a femoral head, wherein the liner has a rim that creates an orifice, and wherein the orifice has a diameter that is smaller than the diameter of the femoral head;
  - (B) a metal shell; and
  - (C) a femoral head.
15. The replacement assembly according to claim 14, wherein the femoral head is integral with or modular on a femoral stem.
16. The replacement assembly according to claim 14, wherein the femoral head is made of a cobalt chrome alloy, stainless steel, or ceramic.
17. The replacement assembly according to claim 15, wherein the femoral stem is made of a cobalt chrome alloy, stainless steel, or titanium.
18. The replacement assembly according to claim 14, wherein the rim extends beyond the center line of the head when the head is enclosed by the liner.
19. The replacement assembly according to claim 14, wherein the metal shell is made of titanium, stainless steel, or a cobalt chrome alloy.
20. The replacement assembly according to claim 14, wherein the femoral head has a large diameter.
21. The replacement assembly according to claim 14, wherein the liner has at least one recess.
22. A method of replacing a hip in a patient in need thereof, comprising the step of surgically implanting in a patient a monopolar acetabular liner or monopolar component that can enclose a femoral head to form a hip replacement prostheses, wherein the liner has a rim that creates an orifice,



- and wherein the orifice has a diameter that is smaller than the diameter of the femoral head.
23. The method according to claim 22, wherein a metal shell also is implanted.
24. The method according to claim 22, wherein a femoral head and stem also are implanted.
25. The method according to claim 22, wherein the rim extends beyond the center line of the head when the head is enclosed by the liner.
26. The method according to claim 22, wherein the liner comprises ultra high molecular weight polyethylene.
27. The method according to claim 26, wherein ultra high molecular weight polyethylene is cross-linked.
28. The method according to claim 27, wherein the cross-linking is performed via irradiation.
29. The method according to claim 22, wherein the femoral head has a large diameter.
30. The method according to claim 22, wherein the liner has at least one recess.
31. A monopolar acetabular liner that can enclose a femoral head to form a hip replacement prostheses, wherein the liner has a rim that creates an orifice and the liner has at least one recess, and wherein the orifice has a diameter that is smaller than the diameter of the femoral head.
32. The monopolar acetabular liner according to claim 31, wherein the liner has at least two recesses.
33. A monopolar acetabular assembly comprising
- (A) a monopolar acetabular liner that encloses a femoral head, wherein the liner has a rim that creates an orifice and the liner has at least one recess, and wherein the orifice has a diameter that is smaller than the diameter of the femoral head; and
  - (B) a metal shell.

34. The monopolar acetabular assembly according to claim 33, wherein the liner has at least two recesses.
35. A hip joint replacement assembly comprising:
- (A) a monopolar acetabular liner that encloses a femoral head, wherein the liner has a rim that creates an orifice and the liner has at least one recess, and wherein the orifice has a diameter that is smaller than the diameter of the femoral head;
  - (B) a metal shell; and
  - (C) a femoral head.
36. The hip joint assembly according to claim 35, wherein the liner has at least two recesses.
37. A method of replacing a hip in a patient in need thereof, comprising the step of surgically implanting in a patient a monopolar acetabular liner or monopolar component that can enclose a femoral head to form a hip replacement prostheses, wherein the liner has a rim that creates an orifice and the liner has at least one recess, and wherein the orifice has a diameter that is smaller than the diameter of the femoral head.
38. The method according to claim 37, wherein the liner has at least two recesses.
39. A constraining ring that is used in conjunction with a monopolar constrained acetabular liner or a cut away monopolar constrained acetabular liner, wherein the ring fits around the perimeter of the monopolar constrained acetabular liner, and wherein the ring is set onto the acetabular liner during the operative procedure after the femoral head is reduced into the acetabular liner.
40. The constraining ring according to claim 39, wherein the shape of the ring is circular.

41. The constraining ring according to claim 39, wherein the ring is made of high strength materials such as cobalt chrome alloy, titanium, or stainless steel.
42. The constraining ring according to claim 39, wherein the ring is a single piece.
43. The constraining ring according to claim 39, has no recess.
44. The constraining ring according to claim 39, has at least one recess.
45. The constraining ring according to claim 39, has at least two recesses.
46. The liner according to claim 39, has no recess.
47. The liner according to claim 39, has at least one recess.
48. The liner according to claim 39, has at least two recesses.
49. A monopolar constrained acetabular liner system with constraining ring assembly comprising:
  - (A) a monopolar acetabular liner that encloses a femoral head, wherein the liner has a rim that creates an orifice, wherein the orifice has a diameter that is smaller than the diameter of the femoral head, wherein a constraining ring fits around the perimeter of the monopolar constrained acetabular liner, wherein the constraining ring is set onto the acetabular liner during the operative procedure after the femoral head is reduced into the acetabular liner; and
  - (B) a metal shell.
50. The assembly according to claim 49, wherein the constraining ring fastens directly to the polyethylene acetabular liner and has no direct contact with the metal shell into which the liner is set.
51. The assembly according to claim 49, wherein the constraining ring is not dependent on the use of a metal shell hence allowing this system to be used with an acetabular liner which is cemented directly into the acetabulum.

52. The assembly according to claim 49, wherein the constraining ring can be secured to the acetabular liner by means of a number of locking mechanisms.
53. The assembly according to claim 49, wherein the shape of the constraining ring is circular.
54. The assembly according to claim 49, wherein the constraining ring is made of high strength materials such as cobalt chrome alloy, titanium, or stainless steel.
55. The assembly according to claim 49, wherein the constraining ring is a single piece.
56. The assembly according to claim 49, wherein the constraining ring has no recess.
57. The assembly according to claim 49, wherein the constraining ring has at least one recess.
58. The assembly according to claim 49, wherein the constraining ring has at least two recesses.
59. The assembly according to claim 49, wherein the liner has no recess.
60. The assembly according to claim 49, wherein the liner has at least one recess.
61. The assembly according to claim 49, wherein the liner has at least two recesses.
62. A hip joint replacement assembly comprising:
  - (A) a monopolar acetabular liner that encloses a femoral head, wherein the liner has a rim that creates an orifice, wherein the orifice has a diameter that is smaller than the diameter of the femoral head, wherein a constraining ring fits around the perimeter of the monopolar constrained acetabular liner, wherein the constraining ring is set onto the

acetabular liner during the operative procedure after the femoral head is reduced into the acetabular liner;

(B) a metal shell; and

(C) a femoral head.

63. The hip joint assembly according to claim 62, wherein the constraining ring fastens directly to the polyethylene acetabular liner and has no direct contact with the metal shell into which the liner is set.
64. The hip joint assembly according to claim 62, wherein the constraining ring is not dependent on the use of a metal shell hence allowing this system to be used with an acetabular liner which is cemented directly into the acetabulum.
65. The hip joint assembly according to claim 62, wherein the constraining ring can be secured to the acetabular liner by means of a number of locking mechanisms.
66. The hip joint assembly according to claim 62, wherein the shape of the constraining ring is circular.
67. The hip joint assembly according to claim 62, wherein the constraining ring is made of high strength materials such as cobalt chrome alloy, titanium, or stainless steel.
68. The hip joint assembly according to claim 62, wherein the constraining ring is a single piece.
69. The hip joint assembly according to claim 62, wherein the constraining ring has no recess.
70. The hip joint assembly according to claim 62, wherein the constraining ring has at least one recess.
71. The hip joint assembly according to claim 62, wherein the constraining ring has at least two recesses.

72. The hip joint assembly according to claim 62, wherein the liner has no recess.
73. The hip joint assembly according to claim 62, wherein the liner has at least one recess.
74. The hip joint assembly according to claim 62, wherein the liner has at least two recesses.
75. A method of replacing a hip in a patient in need thereof, comprising the step of surgically implanting in a patient a monopolar acetabular liner or monopolar component that can enclose a femoral head to form a hip replacement prostheses, wherein the liner has a rim that creates an orifice, wherein the orifice has a diameter that is smaller than the diameter of the femoral head, wherein a constraining ring is used with the monopolar constrained acetabular liner or a cut away monopolar constrained acetabular liner, wherein the constraining ring fits around the perimeter of the constrained acetabular liner, wherein the constraining ring can be set onto the acetabular liner during the operative procedure after the femoral head is reduced into the acetabular liner.
76. The method according to claim 75, wherein the constraining ring fastens directly to the polyethylene acetabular liner and has no direct contact with the metal shell into which the liner is set.
77. The method according to claim 75, wherein the constraining ring is not dependent on the use of a metal shell hence allowing this system to be used with an acetabular liner which is cemented directly into the acetabulum.
78. The method according to claim 75, wherein the constraining ring can be secured to the acetabular liner by means of a number of locking mechanisms.
79. The method according to claim 75, wherein the shape of the constraining ring is circular.

80. The method according to claim 75, wherein the constraining ring is made of high strength materials such as cobalt chrome alloy, titanium, or stainless steel.
81. The method according to claim 75, wherein the constraining ring is a single piece.
82. The method according to claim 75, wherein the constraining ring has no recess.
83. The method according to claim 75, wherein the constraining ring has at least one recess.
84. The method according to claim 75, wherein the constraining ring has at least two recesses.
85. The method according to claim 75, wherein the liner has no recess.
86. The method according to claim 75, wherein the liner has at least one recess.
87. The method according to claim 75, wherein the liner has at least two recesses.
88. A cut away monopolar constrained acetabular liner system with constraining ring assembly comprising: a monopolar acetabular liner that encloses a femoral head, wherein the liner has a rim that creates an orifice, wherein the orifice has a diameter that is smaller than the diameter of the femoral head, wherein a constraining ring is used with the monopolar constrained acetabular liner or the cut away monopolar constrained acetabular liner, wherein the constraining ring fits around the perimeter of the constrained acetabular liner, and wherein the constraining ring is set onto the acetabular liner during the operative procedure after the femoral head is reduced into the acetabular liner.
89. The assembly according to claim 88, wherein the constraining ring fastens directly to the polyethylene acetabular liner.

90. The assembly according to claim 88, wherein the constraining ring is not dependent on the use of a metal shell hence allowing this system to be used with an acetabular liner which is cemented directly into the acetabulum.
91. The assembly according to claim 88, wherein the constraining ring can be secured to the acetabular liner by means of a number of locking mechanisms.
92. The assembly according to claim 88, wherein the shape of the constraining ring is circular.
93. The assembly according to claim 88, wherein the constraining ring is made of high strength materials such as cobalt chrome alloy, titanium, or stainless steel.
94. The assembly according to claim 88, wherein the constraining ring is a single piece.
95. The assembly according to claim 88, wherein the constraining ring has no recess.
96. The assembly according to claim 88, wherein the constraining ring has at least one recess.
97. The assembly according to claim 88, wherein the constraining ring has at least two recesses.
98. The assembly according to claim 88, wherein the liner has no recess.
99. The assembly according to claim 88, wherein the liner has at least one recess.
100. The assembly according to claim 88, wherein the liner has at least two recesses.
101. A hip joint replacement assembly comprising:
  - (A) a monopolar acetabular liner that encloses a femoral head, wherein the liner has a rim that creates an orifice, wherein the orifice has a diameter that is smaller than the diameter of the femoral head, wherein



a constraining ring fits around the perimeter of the monopolar constrained acetabular liner, wherein the constraining ring is set onto the acetabular liner during the operative procedure after the femoral head is reduced into the acetabular liner; and

(B) a femoral head.


102. The hip joint assembly according to claim 101, wherein the constraining ring fastens directly to the polyethylene acetabular liner.
103. The hip joint assembly according to claim 101, wherein the constraining ring is not dependent on the use of a metal shell hence allowing this system to be used with an acetabular liner which is cemented directly into the acetabulum.
104. The hip joint assembly according to claim 101, wherein the constraining ring can be secured to the acetabular liner by means of a number of locking mechanisms.
105. The hip joint assembly according to claim 101, wherein the shape of the constraining ring is circular.
106. The hip joint assembly according to claim 101, wherein the constraining ring is made of high strength materials such as cobalt chrome alloy, titanium, or stainless steel.
107. The hip joint assembly according to claim 101, wherein the constraining ring is a single piece.
108. The hip joint assembly according to claim 101, wherein the constraining ring has no.
109. The hip joint assembly according to claim 101, wherein the constraining ring has at least one recess.
110. The hip joint assembly according to claim 101, wherein the constraining ring has at least two recesses.

111. The hip joint assembly according to claim 101, wherein the liner has no recess.
112. The hip joint assembly according to claim 101, wherein the liner has at least one recess.
113. The hip joint assembly according to claim 101, wherein the liner has at least two recesses.
114. A method of replacing a hip in a patient in need thereof, comprising the step of surgically implanting in a patient a monopolar acetabular liner or monopolar component that can enclose a femoral head to form a hip replacement prostheses, wherein the liner has a rim that creates an orifice, wherein the orifice has a diameter that is smaller than the diameter of the femoral head, wherein a constraining ring is used with a monopolar constrained acetabular liner or a cut away monopolar constrained acetabular liner, wherein the constraining ring fits around the perimeter of the constrained liner, wherein the constraining ring can be set onto the acetabular liner during the operative procedure after the femoral head is reduced into the acetabular liner.
115. The method according to claim 114, wherein the constraining ring fastens directly to the polyethylene acetabular liner.
116. The method according to claim 114, wherein the constraining ring is not dependent on the use of a metal shell hence allowing this system to be used with an acetabular liner which is cemented directly into the acetabulum.
117. The method according to claim 114, wherein the constraining ring can be secured to the acetabular liner by means of a number of locking mechanisms.
118. The method according to claim 114, wherein the shape of the constraining ring is circular.

119. The method according to claim 114, wherein the constraining ring is made of high strength materials such as cobalt chrome alloy, titanium, or stainless steel.
120. The method according to claim 114, wherein the constraining ring is a single piece.
121. The method according to claim 114, wherein the constraining ring has no recess.
122. The method according to claim 114, wherein the constraining ring has at least one recess.
123. The method according to claim 114, wherein the constraining ring has at least two recesses.
124. The method according to claim 114, wherein the liner has no recess.
125. The method according to claim 114, wherein the liner has at least one recess.

FIGURE 1

10






FIGURE 2

30

FIGURE 3  
50





FIG. 3

FIGURE 4

70



Constraining Ring (56) in Different Orientations.

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
7 February 2002 (07.02.2002)


PCT

(10) International Publication Number  
**WO 02/009615 A3**

- (51) International Patent Classification<sup>7</sup>: A61F 2/34, A61L 27/16
- (21) International Application Number: PCT/US01/22638
- (22) International Filing Date: 19 July 2001 (19.07.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/222,049 31 July 2000 (31.07.2000) US  
60/234,345 22 September 2000 (22.09.2000) US  
60/289,528 9 May 2001 (09.05.2001) US
- (71) Applicant (for all designated States except US): MASSACHUSETTS GENERAL HOSPITAL [US/US]; Thirteenth Street, Building 149, Suite 5036, Charlestown, MA 02129-2000 (US).
- (71) Applicants and  
(72) Inventors: HARRIS, William, H. [US/US]; 665 Concord Avenue, Belmont, MA 02178 (US). BURROUGHS, Brian, R. [US/US]; 109A Dartmouth Strasse, Apt.#21, Boston, MA 02114 (US). HOFFEL, Daniel, P. [US/US]; 9180 Heritage Way, Woodbury, MN 55125 (US).
- (74) Agent: ISACSON, John, P.; Heller, Ehrman, White & McAuliffe, 1666 K Street, N.W., Suite 300, Washington, DC 20006 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

[Continued on next page]

(54) Title: ACETABULAR COMPONENTS THAT DECREASE RISKS OF DISLOCATION



(57) Abstract: The present invention provides monopolar acetabular liners (32, 54) that can enclose a femoral head (14) to form a hip replacement prosthesis (30, 50), wherein the liner (32, 54) has a rim (34) that creates an orifice, wherein the orifice has a diameter that is smaller than the diameter of the femoral head (14), and wherein the liner (32, 54) encompasses greater than 50 percent of the volume of the head (14), wherein a constraining ring (56) can be used in conjunction with the monopolar constrained acetabular liner (32, 54) to provide additional support for the femoral head (14) to stay with the acetabular liner (32, 54) and avoid dislocation. Assemblies and complete prosthetic replacements are also provided. Liners (32, 54) and constraining rings (56) having no, one or more recesses (36) also are provided.

WO 02/009615 A3





(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:  
18 July 2002

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— with international search report

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/22638

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 A61F2/34 A61L27/16

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR 1 047 640 A (VAN STEENBRUGGHE) 15 December 1953 (1953-12-15)	1,2,7, 39,40, 42,43,46
Y	the whole document	8,31,32, 88
	---	
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*G\* document member of the same patent family

Date of the actual completion of the international search

22 January 2002

Date of mailing of the international search report

29/01/2002

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2230 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3018

Authorized officer

Klein, C

1

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/22638

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 800 555 A (GRAY, III) 1 September 1998 (1998-09-01)	1-4, 7, 9, 10, 12, 14, 15, 18, 20, 39, 40, 42, 43, 46, 49, 50, 52, 53, 55, 56, 59, 62, 63, 65, 66, 68, 69, 72, 101, 102, 104, 105, 107, 108, 111
Y	the whole document	5, 6, 11, 13, 16, 17, 19, 21, 33-36, 44, 47, 48, 51, 57, 60, 61, 64, 70, 73, 74, 103, 109, 112, 113
Y	WO 97 29793 A (MASSACHUSETTS INSTITUTE OF TECHNOLOGY) 21 August 1997 (1997-08-21) cited in the application the whole document	5, 6
Y	FR 2 430 221 A (GMT GESELLSCHAFT FÜR MEDIZINISCHE TECHNIK) 1 February 1980 (1980-02-01)	8, 13, 21, 31-36, 47, 48, 60, 61, 73, 74, 88, 112, 113
Y	the whole document	
Y	EP 0 234 811 A (PFIZER HOSPITAL PRODUCTS GROUP) 2 September 1987 (1987-09-02) column 2, line 51 - line 56; figures	11, 19
Y	US 5 871 547 A (ABOUAF) 16 February 1999 (1999-02-16) column 6, line 44 - column 7, line 10	16, 17
	-/-	

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/22638

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE 32 00 340 A (HOWMEDICA INTERNATIONAL) 23 September 1982 (1982-09-23) the whole document	44, 57, 70, 109
Y	GB 2 315 222 A (HARDINGE) 28 January 1998 (1998-01-28)	51, 64, 103
A	page 6; figures	16
A	WO 84 03432 A (JOINT MEDICAL PRODUCTS CORPORATION) 13 September 1984 (1984-09-13)	1, 9, 14, 31, 33, 35, 39, 49, 62, 88, 101
	the whole document	
A	FR 2 194 123 A (TORNIER) 22 February 1974 (1974-02-22)	
A	FR 2 395 011 A (DUCROQUET) 19 January 1979 (1979-01-19)	
A	US 4 636 218 A (FUKUURA) 13 January 1987 (1987-01-13)	
A	US 5 044 422 A (LENKER) 3 September 1991 (1991-09-03)	
A	WO 00 07526 A (ESKA IMPLANTS) 17 February 2000 (2000-02-17)	
A	FR 2 785 524 A (SOCIÉTÉ D'ÉTUDES, DE RECHERCHES ET DE FABRICATION S.E.R.F.) 12 May 2000 (2000-05-12)	
A	FR 2 705 883 A (REVEST) 9 December 1994 (1994-12-09)	
A	FR 2 516 377 A (BRÉARD) 20 May 1983 (1983-05-20)	
A	DE 44 28 407 A (KUBEIN-MEESENBURG) 15 February 1996 (1996-02-15)	
P, A	WO 01 05337 A (THE GENERAL HOSPITAL CORPORATION) 25 January 2001 (2001-01-25) cited in the application	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/22638

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 1047640	A	15-12-1953	NONE	
US 5800555	A	01-09-1998	NONE	
WO 9729793	A	21-08-1997	US 5879400 A	09-03-1999
			AU 728605 B2	11-01-2001
			AU 2050697 A	02-09-1997
			CA 2246342 A1	21-08-1997
			CN 1211195 A	17-03-1999
			CZ 9802490 A3	14-04-1999
			EP 0881919 A1	09-12-1998
			JP 2000512323 T	19-09-2000
			PL 328345 A1	18-01-1999
			WO 9729793 A1	21-08-1997
			WO 0105337 A1	25-01-2001
			US 2001027345 A1	04-10-2001
FR 2430221	A	01-02-1980	DE 2829676 A1	24-01-1980
			FR 2430221 A1	01-02-1980
			GB 2029230 A	19-03-1980
			SE 7905815 A	07-01-1980
			US 4279041 A	21-07-1981
EP 234811	A	02-09-1987	US 4718911 A	12-01-1988
			AT 52179 T	15-05-1990
			AU 593062 B2	01-02-1990
			AU 6902387 A	20-08-1987
			CA 1277451 A1	11-12-1990
			DE 3762387 D1	31-05-1990
			DE 8702270 U1	16-07-1987
			EP 0234811 A1	02-09-1987
			IE 59454 B	23-02-1994
			JP 1771545 C	30-06-1993
			JP 4058339 B	17-09-1992
			JP 62217959 A	25-09-1987
			US 4784663 A	15-11-1988
			ZA 8701173 A	28-09-1988
US 5871547	A	16-02-1999	AU 2059197 A	16-09-1997
			EP 0959820 A2	01-12-1999
			JP 11509762 T	31-08-1999
			WO 9731592 A2	04-09-1997
DE 3200340	A	23-09-1982	DE 3200340 A1	23-09-1982
GB 2315222	A	28-01-1998	NONE	
WO 8403432	A	13-09-1984	US 4642123 A	10-02-1987
			US 4678472 A	07-07-1987
			AT 64292 T	15-06-1991
			CA 1264501 A1	23-01-1990
			DE 3484699 D1	18-07-1991
			EP 0137040 A1	17-04-1985
			JP 5050290 B	28-07-1993
			JP 60500657 T	09-05-1985
			WO 8403432 A1	13-09-1984
			US 4950299 A	21-08-1990
			US 4978356 A	18-12-1990

Form PCT/ISA/210 (patent family annex) (July 1992)

BNSDOCID: <WO\_0209815A3\_1>

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/22638

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 8403432	A		US 4960427 A	02-10-1990
			US 6042611 A	28-03-2000
			US 4801301 A	31-01-1989
FR 2194123	A	22-02-1974	FR 2194123 A5	22-02-1974
FR 2395011	A	19-01-1979	FR 2395011 A1	19-01-1979
US 4636218	A	13-01-1987	JP 1412688 C	27-11-1987
			JP 58163354 A	28-09-1983
			JP 62021544 B	13-05-1987
US 5044422	A	03-09-1991	NONE	
WO 0007526	A	17-02-2000	DE 29824009 U1	24-02-2000
			WO 0007526 A1	17-02-2000
FR 2785524	A	12-05-2000	FR 2785524 A1	12-05-2000
FR 2705883	A	09-12-1994	FR 2705883 A1	09-12-1994
			AU 6931994 A	03-01-1995
			EP 0713566 A1	29-05-1996
			WO 9429605 A1	22-12-1994
FR 2516377	A	20-05-1983	FR 2516377 A1	20-05-1983
DE 4428407	A	15-02-1996	DE 4428407 A1	15-02-1996
			AU 3343495 A	07-03-1996
			WO 9604866 A1	22-02-1996
			EP 0774937 A1	28-05-1997
WO 0105337	A	25-01-2001	US 5879400 A	09-03-1999
			AU 728605 B2	11-01-2001
			AU 2050697 A	02-09-1997
			CA 2246342 A1	21-08-1997
			CN 1211195 A	17-03-1999
			CZ 9802490 A3	14-04-1999
			EP 0881919 A1	09-12-1998
			JP 2000512323 T	19-09-2000
			PL 328345 A1	18-01-1999
			WO 9729793 A1	21-08-1997
			WO 0105337 A1	25-01-2001
			US 2001027345 A1	04-10-2001